

Sea Foam Spray

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

Date of issue: 10-01-2019

Version: 4018CA

SECTION 1: Identification

1.1. Product identifier

Product form : Mixture
Product name : Sea Foam Spray
Product code : SS14

1.2. Recommended use and restrictions on use

Recommended uses and restrictions : Engine Treatment/cleaner.
For internal engine use only. Do not spray in the atmosphere.

1.3. Supplier

Manufacturer

Sea Foam International, Inc.
1110 College Drive
Bismarck, ND USA 58501
T 701-751-7363

Supplier

Durkin Enterprises, Inc.
26 Cedar Lane
Mono Ontario L9W 6C8
T 416-259-2699

1.4. Emergency telephone number

Emergency number : +1 (352) 323-3500 (9am-5pm, Mon to Fri (CST))

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

Classification (GHS CA)

Flam. Aerosol 2	H223
Press. Gas (Comp.)	H280
Skin Irrit. 2	H315
Eye Irrit. 2A	H319
STOT SE 3	H336
Asp. Tox. 1	H304

2.2. GHS Label elements, including precautionary statements

GHS-CA labelling

Hazard pictograms (GHS-CA) :



Signal word (GHS CA) : Danger

Hazard statements (GHS-CA) :

H223 - Flammable aerosol.
H280 - Contains gas under pressure; may explode if heated.
H304 - May be fatal if swallowed and enters airways.
H315 - Causes skin irritation.
H319 - Causes serious eye irritation.
H336 - May cause drowsiness or dizziness.

Precautionary statements (GHS-CA) :

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211 - Do not spray on an open flame or other ignition source.
P251 - Do not pierce or burn, even after use.
P261 - Avoid breathing dust, fume, gas, mist, spray, vapours.
P264 - Wash hands thoroughly after handling.
P271 - Use only outdoors or in a well-ventilated area.
P280 - Wear eye protection, face protection, protective clothing, protective gloves.
P301+P310 - IF SWALLOWED: Immediately call a POISON CENTER or doctor.
P331 - Do NOT induce vomiting.
P302+P352 - IF ON SKIN: Wash with plenty of water.
P362+P364 - Take off contaminated clothing and wash it before reuse.
P332+P313 - If skin irritation occurs: Get medical advice/attention.
P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P312 - Call a POISON CENTER or doctor if you feel unwell.
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337+P313 - If eye irritation persists: Get medical advice/attention.
P405 - Store locked up.
P403 - Store in a well-ventilated place.

Sea Foam Spray

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation

2.3. Other hazards

No additional information available

2.4. Unknown acute toxicity (GHS CA)

Not applicable

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	% wt
Petroleum distillates	*	*
Hydrocarbon-based solvent	*	*
Isopropyl alcohol	(CAS-No.) 67-63-0	10 - 30

Comments *Chemical ingredient identity and/or concentration information withheld for some or all components present is confidential business information. HMIRA Registry Number: 03343843 - Filing Date: 2019.10.01

SECTION 4: First-aid measures

4.1. Description of first aid measures

- First-aid measures after inhalation : If inhaled and if breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell.
- First-aid measures after skin contact : If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. Wash clothing before re-using. Get medical attention if irritation develops and persists.
- First-aid measures after eye contact : IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
- First-aid measures after ingestion : IF SWALLOWED: Immediately call a POISON CENTER/doctor. Do NOT induce vomiting. Never give anything by mouth to an unconscious person.

4.2. Most important symptoms and effects (acute and delayed)

- Symptoms/effects after inhalation : May cause irritation to the respiratory tract. May cause drowsiness or dizziness.
- Symptoms/effects after skin contact : Causes skin irritation. Symptoms may include redness, drying, defatting and cracking of the skin.
- Symptoms/effects after eye contact : Causes serious eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with marked redness and swelling of the conjunctiva.
- Symptoms/effects after ingestion : May be fatal if swallowed and enters airways. May result in aspiration into the lungs, causing chemical pneumonia. May cause gastrointestinal irritation, nausea, vomiting and diarrhea.

4.3. Immediate medical attention and special treatment, if necessary

- Other medical advice or treatment : Symptoms may be delayed. In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

- Suitable extinguishing media : Dry chemical. Foam. Carbon dioxide (CO₂). Water fog.

5.2. Unsuitable extinguishing media

- Unsuitable extinguishing media : Do not use a solid water stream as it may scatter and spread fire.

5.3. Specific hazards arising from the hazardous product

- Fire hazard : Flammable aerosol. Products of combustion may include, and are not limited to: oxides of carbon. Nitrogen oxides. Sulphur oxides. Other unidentified organic compounds. Toxic and irritating gases may be released. Will float and can be reignited on water surface.
- Explosion hazard : May form flammable/explosive vapour-air mixture. Heavier than air, vapours may travel long distances along ground, ignite and flash back to source.

5.4. Special protective equipment and precautions for fire-fighters

- Firefighting instructions : Use water spray to cool exposed surfaces.
- Protection during firefighting : Keep upwind of fire. Wear full fire fighting turn-out gear (full Bunker gear) and respiratory protection (SCBA).

Sea Foam Spray

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to unnecessary and unprotected personnel. Use special care to avoid static electric charges. Remove all sources of ignition.

6.2. Methods and materials for containment and cleaning up

For containment : Stop leak if safe to do so. Eliminate every possible source of ignition. Absorb and/or contain spill with inert material (sand, vermiculite or other appropriate material), then place in suitable container. Do not flush into surface water or sewer system. Wear recommended personal protective equipment.

Methods for cleaning up : Sweep or shovel spills into appropriate container for disposal. Provide ventilation.

6.3. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection"

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Avoid contact with skin and eyes. Avoid breathing dust/fume/gas/mist/vapours/spray. Do not swallow. Handle and open container with care. When using do not eat, drink or smoke. Keep away from sources of ignition - No smoking. Take precautionary measures against static discharge. Use only non-sparking tools. Use only outdoors or in a well-ventilated area.

Hygiene measures : Wash contaminated clothing before reuse. Always wash hands after handling the product.

Additional hazards when processed : Handle empty containers with care because residual vapours are flammable.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Proper grounding procedures to avoid static electricity should be followed.

Storage conditions : Keep out of the reach of children. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Store in a dry, cool and well-ventilated place. Store locked up.

Incompatible materials : Strong oxidizing agents.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Petroleum distillates		
USA - ACGIH	ACGIH TWA (mg/m ³)	5 mg/m ³ 8 hr (oil mist)
USA - ACGIH	ACGIH STEL (mg/m ³)	10 15 min (oil mist)
Isopropyl alcohol (67-63-0)		
USA - ACGIH	ACGIH TWA (ppm)	200 ppm
USA - ACGIH	ACGIH STEL (ppm)	400 ppm

8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.

Environmental exposure controls : Avoid release to the environment.

8.3. Individual protection measures/Personal protective equipment

Hand protection:

Wear chemically resistant protective gloves.

Eye protection:

Wear approved eye (properly fitted dust- or splash-proof chemical safety goggles) / face (face shield) protection.

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

Other information:

Handle in accordance with good industrial hygiene and safety procedures. Do not eat, drink or smoke when using this product.

Sea Foam Spray

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Clear liquid. Aerosol
Colour	: Clear
Odour	: Petroleum hydrocarbon
Odour threshold	: No data available
pH	: No data available
Relative evaporation rate (butylacetate=1)	: < 1
Relative evaporation rate (ether=1)	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: 82.2 °C
Flash point	: 12.8 °C (Concentrate) TCC
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: Flammable aerosol.
Vapour pressure	: 80-90 psig
Vapour pressure at 50 °C	: No data available
Relative vapour density at 20 °C	: > 1 Heavier than air
Relative density	: 0.8
Solubility	: Slightly soluble Water: 0.1 - < 1.0 %
Partition coefficient n-octanol/water	: No data available
Viscosity, kinematic	: No data available
Explosive limits	: No data available

9.2. Other information

VOC content	: 367 g/l
-------------	-----------

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity	: No dangerous reactions known under normal conditions of use.
Chemical stability	: Stable under normal conditions. May form flammable/explosive vapour-air mixture.
Possibility of hazardous reactions	: No dangerous reactions known under normal conditions of use.
Conditions to avoid	: Heat. Sources of ignition. Direct sunlight. Incompatible materials.
Incompatible materials	: Strong oxidizing agents. Strong acids. Strong bases.
Hazardous decomposition products	: May include, and are not limited to: oxides of carbon. Nitrogen oxides. Sulphur oxides. Other unidentified organic compounds. Toxic and irritating gases may be released. May release flammable gases.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral)	: Not classified.
Acute toxicity (dermal)	: Not classified.
Acute toxicity (inhalation)	: Not classified.

Petroleum distillates	
LD50 oral rat	> 5000 mg/kg
LD50 dermal rabbit	> 2000 mg/kg
Hydrocarbon-based solvent	
LD50 oral rat	> 5000 mg/kg
LD50 dermal rabbit	> 3160 mg/kg
LC50 inhalation rat	73680 ppm/4h
Isopropyl alcohol (67-63-0)	
LD50 oral rat	5045 mg/kg
LD50 dermal rabbit	4059 mg/kg
LC50 inhalation rat	72600 mg/m ³ (Exposure time: 4 h)

Sea Foam Spray

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

Skin corrosion/irritation	: Causes skin irritation.
Serious eye damage/irritation	: Causes serious eye irritation.
Respiratory or skin sensitization	: Not classified.
Germ cell mutagenicity	: Not classified.
Carcinogenicity	: Not classified.
Reproductive toxicity	: Not classified.
STOT-single exposure	: May cause drowsiness or dizziness.
STOT-repeated exposure	: Not classified.
Aspiration hazard	: May be fatal if swallowed and enters airways.

Sea Foam Spray	
Vaporizer	Aerosol
Symptoms/effects after inhalation	: May cause irritation to the respiratory tract. May cause drowsiness or dizziness.
Symptoms/effects after skin contact	: Causes skin irritation. Symptoms may include redness, drying, defatting and cracking of the skin.
Symptoms/effects after eye contact	: Causes serious eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with marked redness and swelling of the conjunctiva.
Symptoms/effects after ingestion	: May be fatal if swallowed and enters airways.;May result in aspiration into the lungs, causing chemical pneumonia;May cause gastrointestinal irritation, nausea, vomiting and diarrhea
Other information	: Likely routes of exposure: ingestion, inhalation, skin and eye.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : May cause long-term adverse effects in the aquatic environment.

Petroleum distillates	
LC50 fish 1	> 5000 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss)
EC50 Daphnia 1	> 1000 mg/l (Exposure time: 48 h - Species: Daphnia magna)

Isopropyl alcohol (67-63-0)	
LC50 fish 1	9640 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
LC50 fish 2	11130 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])
EC50 Daphnia 1	13299 mg/l (Exposure time: 48 h - Species: Daphnia magna)
EC50 72h algae (1)	> 1000 mg/l (Species: Desmodesmus subspicatus)
EC50 96h algae (1)	> 1000 mg/l (Species: Desmodesmus subspicatus)

12.2. Persistence and degradability

Sea Foam Spray	
Persistence and degradability	Not established.

12.3. Bioaccumulative potential

Sea Foam Spray	
Bioaccumulative potential	Not established.

Isopropyl alcohol (67-63-0)	
Partition coefficient n-octanol/water	0.05 (at 25 °C)

12.4. Mobility in soil

Isopropyl alcohol (67-63-0)	
Partition coefficient n-octanol/water	0.05 (at 25 °C)

12.5. Other adverse effects

Ozone : Not classified.
Other information : No other effects known.

SECTION 13: Disposal considerations

13.1. Disposal methods

Product/Packaging disposal recommendations : Dispose in a safe manner in accordance with local/national regulations.
Additional information : Handle empty containers with care because residual vapours are flammable. Do not pressurize, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition.

Sea Foam Spray

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

SECTION 14: Transport information


14.1. Basic shipping description

In accordance with TDG

Transportation of Dangerous Goods

UN-No. (TDG) : UN1950
TDG Primary Hazard Classes : 2.1 - Class 2.1 - Flammable Gas.
Transport document description : UN1950 AEROSOLS, 2.1
Proper Shipping Name (Transportation of Dangerous Goods) : AEROSOLS, Limited Quantity

Hazard labels (TDG) :



TDG Special Provisions : 80 - Despite section 1.17 of Part 1, Coming into Force, Repeal, Interpretation, General Provisions and Special Cases, a person must not offer for transport or transport these dangerous goods unless they are in a means of containment that is in compliance with section 5.11 of Part 5, Means of Containment, except that the requirement for aerosol containers to be tightly packed in a wood, fibreboard or plastic box does not apply to a user or purchaser who transports no more than six aerosol containers. For a similar rule respecting aerosol containers, see subparagraph 1.15(1)(a)(i) of Part 1, Coming into Force, Repeal, Interpretation, General Provisions and Special Cases. SOR/2012-245
107 - (1)These Regulations, except for Part 1 (Coming into Force, Repeal, Interpretation, General Provisions and Special Cases) and Part 2, (Classification), do not apply to the handling, offering for transport or transporting of UN1950, AEROSOLS, and UN2037, GAS CARTRIDGES, that contain dangerous goods included in Class 2.1 or Class 2.2 and that are transported on a road vehicle, a railway vehicle or a ship on a domestic voyage, if the aerosols or gas cartridges have a capacity less than or equal to 50 mL. (2)Subsection (1) does not apply to self-defence spray. SOR/2014-306

Explosive Limit and Limited Quantity Index : 1 L
Excepted quantities (TDG) : E0
Passenger Carrying Road Vehicle or Passenger Carrying Railway Vehicle Index : 75 L

14.2. Transport information/DOT

No additional information available

14.3. Air and sea transport

No additional information available

SECTION 15: Regulatory information

15.1. National regulations

All components of this product are listed, or excluded from listing, on the Canadian DSL (Domestic Substances List) and NDSL (Non-Domestic Substances List) inventories.

15.2. International regulations

No additional information available

SECTION 16: Other information

Disclaimer: We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.